


W005G THRU W10G

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

Reverse Voltage - 50 to 1000 Volts Forward Current - 1.5 Amperes


Case Style W0G



Dimensions in inches and (millimeters)

FEATURES

- ◆ Plastic material has Underwriters Laboratory Flammability Recognition 94V-0
- ◆ This series is UL listed under the Recognized Component Index, file number E54214
- ◆ Glass passivated chip junctions
- ◆ High case dielectric strength
- ◆ Typical I_R less than $0.1\mu A$
- ◆ High overload surge capability
- ◆ Ideal for printed circuit boards
- ◆ High temperature soldering guaranteed:
260°C/10 seconds, 0.375" (9.5mm) lead length, 5lbs (2.3kg) tension



MECHANICAL DATA

Case: Molded plastic body over passivated junctions

Terminals: Plated leads solderable per MIL-STD-750, Method 2026

Mounting Position: Any

Weight: 0.04 ounce, 1.1 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	W005G	W01G	W02G	W04G	W06G	W08G	W10G	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current at 0.375" (9.5mm) lead length at $T_A=25^\circ C$	I_{AV}	1.5							Amps
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	50.0							Amps
Rating for fusing ($t < 8.3ms$)	I^2t	10.0							A ² sec
Maximum instantaneous forward voltage drop per leg at 1.0A	V_F	1.0							Volts
Maximum DC reverse current at rated $T_A=25^\circ C$ DC blocking voltage per leg $T_A=125^\circ C$	I_R	5.0 500.0							μA
Typical junction capacitance per leg (NOTE 1)	C_J	14.0							pF
Typical thermal resistance per leg (NOTE 2)	$R_{\theta JA}$ $R_{\theta JL}$	36.0 11.0							$^\circ C/W$
Operating junction temperature range	T_J	-55 to +150							$^\circ C$
Storage temperature range	T_{STG}	-55 to +150							$^\circ C$


NOTES:

(1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts


(2) Thermal resistance from junction to ambient and from junction to lead at 0.375" (9.5mm) lead length P.C.B. mounting

RATINGS AND CHARACTERISTICS CURVES W005G THRU W10G


**FIG. 1 - DERATING CURVE
OUTPUT RECTIFIED CURRENT**




**FIG. 2 - MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT PER LEG**



**FIG. 3 - TYPICAL FORWARD CHARACTERISTICS
PER LEG**



**FIG. 4 - TYPICAL REVERSE CHARACTERISTICS
PER LEG**



**FIG. 5 - TYPICAL JUNCTION CAPACITANCE
PER LEG**




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE

